

TECHNICAL SPECIFICATIONS

FABRICATION AND INSTALLATION OF ATM SUNSHADE

Steel Specifications:

- 2" outside diameter stainless steel pipe (6m length)
- 6mm x 20mm stainless clip (for polycarbonate)
- 6mm cover plate
- Stainless steel countersunk screw
- Consumables

Sunshade:


- 6mm thk x 1.2m x 2.4m twin wall polycarbonate sheet (color: sultan blue)
- Decorative sticker DBP logo & ATM

Dimensions: See attached plan and elevation

Notes:


1. Contractor must conduct an inspection and verify the actual measurements on-site.
2. Contractor must touch-up, repair or replace damages made on new or existing bank properties before substantial completion.
3. Contractor must remove left over materials and debris from work area.
4. Contractor must comply with COVID-19 protocols inside DBP premises.

Prepared by:


MARVIN ANTHONY D. LUCAS
PDO II, Projects and Contracts Management Unit

Reviewed by:


AM MICHAEL ANTOLIN F. CANCIO
Head, VisMin Team-PCMU


ENGR. JOSE FRANCISCO E. PEREZ
Acting Head, PCMU
Per Office Order No. 234 dtd July 1, 2021

Endorsed by:


AVP JOSE C. DELA FUENTE
Acting Head, Construction & Facilities Management Department
Per Office Order No. 234 dtd July 1, 2021