



INVITATION/ REQUEST FOR SUBMISSION OF PRICE QUOTATIONS
(Posted in the PHILGEPS/DBP Website/ Conspicuous Places of the Procuring Entity)

The Development Bank of the Philippines, through the Regional- Bids & Award Committee (RBAC-Eastern Visayas) invites interested parties to submit price quotations for the Supply, Delivery, Installation & Commissioning of the DBP Maasin Branch CCTV Camera, to wit:

Specification/Description	No. of Units	Mode of Procurement	Approved Budget
Upgrade of CCTV Camera	1 lot	Small Value Procurement	350,000.00
TOTAL ABC			350,000.00

SPECIFICATIONS

Please refer to the attached Specifications and Details Requirement of the Branch

Location of the Project: DBP Maasin Branch, R. Kangleon St., Brgy. Tunga-tunga, Maasin City

**Additional Instructions: 1. Sign each & every page of the Technical Specifications
2. Delivery of the item should be direct to the addresses below.**

NOTE: PROPOSAL SHALL INCLUDE THE DELIVERY/INSTALLATION CHARGES AND ALL APPLICABLE TAXES.

The Supplier shall complete all works within Thirty (30) calendar days upon receipt of Purchase Order (PO)/Notice to Proceed (NTP).

Deadline for the submission of price quotations shall be on or before 10-24-2022 at 1:00 p.m.

Only price quotations from Filipino citizens or companies duly registered with the Department of Trade and Industry or Securities and Exchange Commission, with current business permits and those that are PHILGEPS registered, shall be accepted.

Development Bank of the Philippines reserves the right to reject any and all bids/price quotations, waive any defect in them, and award to the bidder/participant whose bid/price quotation is the most advantageous to the Bank

signed
SM PAUL C. MATIENZO
Chairman, RBAC-EV

TECHNICAL SPECIFICATION

CCTV CAMERA - DBP Maasin Branch

Dome Camera

- 5MP Fix IP Dome Camera real time video recording
- Lens : IRI Series – 3.6mm
- Angle View : 76' (3.6mm)
- Housing : Weather Proof IP66 rated
- Indoor/outdoor
- IR Distance 10m-20m

Bullet Camera

- 5MP real time video recording
- Lens : IRI Sereis – 3.6mm
- Angle View : 76' (3.6mm)
- Housing : Weather Proof IP66 rated
- Indoor/outdoor
- Distance 10m-15m

16 CHANNEL DVR/NVR

- H.265 + Video Compression/Third part camera supported
- 5 Megapixels resolution recording
- HDMI and VGA output 2560 * 1920 P resolution
- 8/16 ch synchronous playback
- HDD quota and group management
- Hard Drive capacity, to meet the 90 days (real time) retention period

Hard Drive

Formatted NTFS for Windows 10, Windows 8, windows 7. Requires reformatting for Mac OS X. Compatibility may vary depending on user's hardware configuration and operating system.

- Interface – USB 3.0, USB 2.0
- Operating System – Windows and MAC
- Package Includes – WD Elements hard drive, USB cable, AC Adapter, Quick install guide.

16 Channel CCTV Camera Power Supply – 12 VDC – 10 Amps.

Every channel is protected with Auto-reset PTC fuses, which means these fuses will not blow. This box can be mounted to any surface, plugged into AC outlet.

- 12VDC – 10Amp supply current
- Multiple outputs (16 Channel)
- 16 – Auto-reset PTC fuse protected output
- Power on/off switch
- DC regulated, over current and voltage protected
- Individual LED indicator for each output
- Fuse Rating: 1. 1A

Power Interface Switch for Power Over Ethernet (PoE) Powered Devices (IF Require by the contractor/installer)

Features:

- Integrated Power Interface Switch for IEEE
- Provide PD Detection Signature
- Provides PD Classification signature
- Programmable Inrush Current Limit
- Internal 0.3 - Ω Low - side FET
- Interface to DC/DC Soft-start for DC / DC Enable
- Internal Thermal Protection – Disconnects PD Load
- Minimal External Parts Count
- 8 – Pin SOIC. 8-Pin TSSOP Packages

NOTE : The Following excluded

1. Installation cost, per diem and transportation allowance
2. VAT
3. Cable, wires, pipes and other accessories to complete the project

Prepared By:

APPROVED: