



Central Portal for
Philippine Government
Procurement Opportunities

Bid Notice Abstract

Request for Quotation (RFQ)

Reference Number 9219963
Procuring Entity DEVELOPMENT BANK OF THE PHILIPPINES - CENTRAL LUZON
Title SUPPLY, DELIVERY, INSTALLATION AND TESTING OF SEVEN (7) LOTS GLASS BREAK SENSORS AND DETECTORS FOR BBG-CL BRANCHES

Area of Delivery

Solicitation Number: 2022-11	Status	Active
Trade Agreement: Implementing Rules and Regulations	Associated Components	2
Procurement Mode: Negotiated Procurement - Small Value Procurement (Sec. 53.9)	Bid Supplements	0
Classification: Goods	Document Request List	0
Category: Security Surveillance and Detection Equipment	Date Published	11/11/2022
Approved Budget for the Contract: PHP 240,000.00	Last Updated / Time	11/11/2022 00:00 AM
Delivery Period: 20 Day/s	Closing Date / Time	15/11/2022 17:00 PM
Client Agency:		
Contact Person: May Villanueva Mendoza RBAC for Central Luzon Secretariat Mc Arthur Hi-way, Dolores San Fernando City Pampanga Philippines 2000 63-63- 63-045-9631232 clbg@dbp.ph		

Description

SUPPLY, DELIVERY, INSTALLATION AND TESTING OF SEVEN (7) LOTS GLASS BREAK SENSORS AND DETECTORS FOR CABANATUAN, CLARK, MALOLOS, PALAYAN, SAN FERNANDO PAMPANGA AND VALENZUELA BRANCHES AND SAN JOSE DEL MONTE BRANCH LITE UNIT

UNIT / BRANCH - ABC
Cabanatuan Branch 55,000.00

Clark Branch 25,000.00

Malolos Branch 40,000.00
Palayan Branch 25,000.00

San Fernando Pampanga Branch 50,000.00
San Jose Del Monte BLU 25,000.00
Valenzuela Branch 20,000.00
Total 240,000.00

Project will be awarded to the Supplier with the lowest total quoted price, subject to the condition that quoted price shall not exceed the set ABC per unit/branch.

TECHNICAL SPECIFICATIONS

LOOP VOLTAGE 3 VDC minimum to 20 VDC maximum

LOOP CURRENT 100 mA maximum

POWER REQUIREMENTS Less than 1 mS

TRANSIENT SUSPENSION 600 watts for 1 mS

ALARM OUTPUT TYPE Normally-closed solid state output, non-polarized

ALARM OUTPUT RESISTANCE 20 Ω maximum (closed/non-alarm condition)

1 MΩ minimum (open/alarm condition)

ALARM OUTPUT TIMING Open for 1 second minimum during an alarm condition

WIRING LEADS 22 AWG, 2 conductor zip cord

COLOR White

Created by May Villanueva Mendoza

Date Created 10/11/2022

The PhilGEPS team is not responsible for any typographical errors or misinformation presented in the system. PhilGEPS only displays information provided for by its clients, and any queries regarding the postings should be directed to the contact person/s of the concerned party.