

Head Office: Sen. Gil J. Puyat Avenue corner Makati Avenue, Makati City, Philippines

ANNEX "A"

DEVELOPMENT BANK OF THE PHILIPPINES **TERMS OF REFERENCE** Fire Proof CASH SAFE Vault for DBP Masbate Branch

Mode of Procurement: Small-Value Procurement

Approved Budget for the Contract: <u>₽ 200,000.00</u> (inclusive of VAT /applicable taxes) 1.

Item	Quantity	Unit Cost	Total Cost
Fire Proof cash safe vault	1	200,000.00	200,000.00

11. **Technical Specifications**

Fire Proof cash safe vault

- > Fire Resistance: At least Two-hour fire resistance and can withstand heat exposure up to 1,500 degrees Fahrenheit.
- Outside Overall Dimensions: At least 70" height x 39" width x 29" depth
- ➤ Inside Clear Dimensions: At least 60"height x 32" width x 18" depth
- Overall Door Thickness: 3.5-4" thick excluding handle
- Hinges: Pin-type hinges made of heavy rolled by steel with thrust washers.
- > Protection Lock: The locking mechanism is controlled by a three-tumbler keychanging combination locks, listed by the Underwriters' Laboratories, Inc. Each lockset is capable of 1,000.000 changes.
- > Boltwork: The door is fitted with at least ten (10) sliding, solid stainless steel locking bolts and rear jamb. These locking bolts should measure 1/2- 3/4" in diameter.
- With Automatic Bolt Lock
- Mechanical: A relocking mechanism attached to the combination lockset will activate when an attack is mounted against the lock itself.
- Finish: Textured with color
- Net Weight: 800-880 kgs.
- Gross Weight: 1,000-1,100 kgs.

Auxiliary Fire proof cash safe

- > Fire Resistance: At least Two-hour fire resistance and can withstand heat exposure up to 1,500 degrees Fahrenheit.
- > Outside Overall Dimensions: at least 40" height x 20" width x 22" depth
- ➤ Inside Clear Dimensions: at least 30" height x 15" width x 14" depth
- Overall Door Thickness: 3 to 4" thick excluding handle









DEVELOPMENT BANK OF THE PHILIPPINES

Head Office: Sen. Gil J. Puyat Avenue corner Makati Avenue, Makati City, Philippines

- Hinges: Pin-type hinges made of heavy rolled by steel with thrust washers
- Protection Lock: The locking mechanism is controlled by a three-tumbler keychanging combination locks, listed by the Underwriters' Laboratories. Inc. Each lockset is capable of 1,000.000 changes.
- Boltwork: The door is fitted with at least three (3) sliding, solid stainless steel locking bolts and rear jamb. These locking bolts measure 1/2-3/4" in diameter.
- With Automatic Bolt lock.
- Mechanical: A relocking mechanism attached to the combination lockset will activate when an attack is mounted against the lock itself.
- Interior Units: Two utility drawers
- > Finish: Textured with color
- Net weight: from 250-280 kgs.
- Gross Weight: from 300-350 kgs.

III. Conditions of the Contract

- The Supplier shall ensure that the items delivered are in accordance with the specifications required by the DBP. DBP has the right to reject delivery if the item/s delivered were found to be defective and not in accordance with the required specifications/model.
- 2. DBP may terminate/cancel the Purchase Order (PO)/Notice to Proceed (NTP) when the Supplier fails to deliver, perform and comply with its obligation.
- 3. Delivery Period: The Supplier shall deliver the items within sixty (60) calendar days after receipt of PO.
- 4. Point of Delivery: DBP Masbate Branch, Danao cor Mabini Street, Masbate City.

IV. Documentary Requirements:

Interested Supplier/s must submit the following:

- a. Proposal/Quotation
- b. Proof of PHILGEPS Registration
- c. 2022 Mayor's/Business Permit

V. Payment:

- Payment shall be processed after completion of delivery subject to complete documents for payment (i.e. Billing Statement/Statement of Account, Certificate of Completion/Acceptance, if applicable).
- For every day of delay, 1/10 of 1% of the price of undelivered quantity shall be deducted from the payment, in case the Supplier fails to deliver the items on time.