



DEVELOPMENT BANK OF THE PHILIPPINES  
Head Office: Sen. Gil J. Puyat Avenue corner  
Makati Avenue, Makati City, Philippines

REQUEST FOR QUOTATION  
FOR

SUPPLY, DELIVERY, INSTALLATION AND TESTING OF CCTV SURVEILLANCE SYSTEM FOR  
BBG CEV OH, CARCAR, UBAY, DOLORES AND TACLOBAN BRANCHES

1. The DEVELOPMENT BANK OF THE PHILIPPINES BRANCH BANKING GROUP-CENTRAL & EASTERN VISAYAS (DBP BBG-CEV) through the CORPORATE BUDGET OF DBP FOR CY 2025 intends to apply the sum of **One Million Four Hundred Thousand Pesos Only (Php 1,400,000.00)**.

Item Description	End – User	Quantity	Approved Budget Cost
Supply, Delivery, Installation and Testing of CCTV Surveillance System	BBG CEV – OH	1	Php 1,400,000.00  <i>Inclusive of labor fees and all applicable charges</i>
	Carcar Branch	1	
	Ubay Branch	1	
	Dolores Branch	1	
	Tacloban Branch	1	

Note:

- Conditions stated in the technical specification shall be applied to the item listed above
- Proposal shall include the labor fees and all applicable charges
- Payment: No downpayment. Processing of payment via check shall only proceed upon complete delivery.

The deadline for the submission of price quotations shall be on or before Sept. 30, 2025 at DBP Cebu Bldg. Osmena Boulevard, Cebu City, Cebu. Please contact **Azenith Jaymil A. Lumabi** at telephone numbers **(032) 255-6325**. You may also email your proposal/quotation at **cevbgb@dbp.ph**

Only price quotations from Filipino citizens or companies duly registered with the Department of Trade and Industry or Securities and Exchange Commission, with current business permits and those that are PHILGEPS registered shall be accepted.

Development Bank of the Philippines, BBG-Central and Eastern Visayas, reserves the right to reject any and all bids/price quotations, to waive any defect in them and to award to the bidder/participant whose bid/price quotation is the most advantageous to the Bank.


**SM CHRIST E. VALDEHUEZA**  
Chairman, RBAC CV

## TECHNICAL SPECIFICATION – CCTV SURVEILLANCE SYSTEM


Components/Particulars	CCTV Surveillance System	
	16-Channel	32-Channel
<b>5MP Dome Type Camera</b>		
- Camera Resolution	5MP @ 20fps, 4MP @25/30fps	
- Built-in IR LED	Yes	
- Lens Type	Fixed-focal	
- Focal Length	2.8mm; 3.6mm	
- Feature	Motion Detection	
- Network	Open Network Video Interface (ONVIF)	
- Power Supply	12V DC/PoE	
- Protection	Not less than IP66	
- Inclusive	Junction box, mounting bracket/s, other accessories necessary to operate the camera	
<b>5MP Bullet Type Camera</b>		
- Camera Resolution	5MP @ 20fps, 4MP @25/30fps	
- Built-in IR LED	Yes	
- Lens Type	Fixed-focal	
- Focal Length	2.8mm; 3.6mm	
- Feature	Motion Detection	
- Network	Open Network Video Interface (ONVIF)	
- Power Supply	12V DC/PoE	
- Protection	Not less than IP66	
- Inclusive	Junction box, mounting bracket/s, other accessories necessary to operate the camera	
<b>Network Video Recorder w/ Internal HDD</b>		
- Capacity	To meet 60 days' real-time retention period	
	<ul style="list-style-type: none"> <li>- Interface : SATA</li> <li>- Cache : ≥256MB</li> <li>- Transfer Rate : ≥230MB/s</li> <li>- Operating Temp. : ≤65°C</li> </ul>	
- SATA Port	≥ 4 SATA ports, ≥ 8TB per disk	
- Channel Playback	16-Channel	32-Channel
- Resolution	5MP	
- Video Output	HDMI and VGA	

- Video Compression	H.265+/H.265	
- Multi-screen Display	Yes	
- Network	Open Network Video Interface (ONVIF)	
- Power Supply	100 to 240V AC, 50/60 Hz	
<b>Back-up External Hard Drive w/ Attached Storage</b>		
- Capacity	To meet 60 days' real-time retention period	
	- Interface	: SATA
	- Cache	: ≥256MB
	- Transfer Rate	: ≥230MB/s
	- Operating Temp.	: ≤65°C
- Interface	USB	
- Power Supply	100 to 240V AC, 50/60 Hz	
- Inclusive	USB cable, AC adapter, and quick install guide	
<b>Wall-mounted 9U CCTV Cabinet</b>		
- Color	Black, powder-coated Finish	
- Built-in fan	Yes	
- Inclusive	Lock and keys, fixed trays, and other mounting accessories	
<b>32" CCTV Monitor</b>		
- Display	LED backlight	
- Resolution	≥ 1080P	
- Inputs	1-VGA, 1-HDMI (minimum input)	
- Aspect Ratio	16:9	
- Power Supply	100 to 240V AC, 50/60 Hz	
- Inclusive	Standard mounting brackets and stand	
<b>Power over Ethernet (POE) Switch</b>		
- No. of Ports	≥16	32
- Interface	100Mb/s ports	
- Long Distance Transmission	≥ 250m	
- Power Supply	100 to 240V AC, 50/60 Hz	
- Inclusive	Necessary accessories	


Recommended by:




**ANGELIE G. FALCONITE**  
TWG Chairman



**ANNIE P. TUMALAK**  
TWG Vice Chairman



**REX T. TINETA**  
TWG Member



**IRENE T. ARCHIVAL**  
TWG Member



**RONA O. LORA**  
TWG Member

Approved by:

**SVP HELBERT ANTOINE A. ACHAY**  
Head of Procuring Entity